

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 42 E., MDM, NEVADA

CHAINS		
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a steel fence post firmly set and exposed 4 ft. above ground, alongside the iron post, with brass cap mkd.</p>	
	<p style="text-align: center;">T34N R42E R43E S 24 S 19 S 25 S 30</p>	
	<p style="text-align: center;">1971</p>	
	<p>S. 89° 17' W., bet. secs. 24 and 25.</p>	
	<p>Over gently rolling land, through shadscale.</p>	
4.00	<p>Ravine, drains NNE.; asc. 20 ft. over NE. slope.</p>	
31.00	<p>Slope changes; asc. 120 ft. over E. slope.</p>	
38.00	<p>Ridge, bears SSE. and NNW.; desc. 10 ft. over W. slope.</p>	
40.19	<p>The ¼ sec. cor. of secs. 24 and 25, monumented with the original sandstone, 17x6x4 ins., mkd. ¼ on the N. face, firmly set in a mound of stone.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T34N R42E S 24 ¼ ——— S 25</p>	
	<p style="text-align: center;">1972</p>	
	<p>bury the marked stone and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p>	
	<p style="text-align: center;">—————</p>	
	<p>S. 89° 05' W., beginning new measurement.</p>	
	<p>Over rolling land, desc. 60 ft. over W. slope.</p>	
5.30	<p>Ravine, drains NNE.; asc. 160 ft. over E. slope.</p>	
37.91	<p>The cor. of secs. 23, 24, 25 and 26.</p>	
	<p>N. 0° 45' W., bet. secs. 23 and 24.</p>	
	<p>Over rolling land, through shadscale; desc. 10 ft. over E. slope.</p>	