

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 34 N., R. 43 E.

CHAINS

- 16.40 Trail road, bears SSE. and NNW.
- 22.50 Wash, 15 lks. wide, 2 ft. deep, drains NNW.
- 39.10 Ditch, 60 lks. wide, 4 ft. deep, course NW.
- 39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T34N
R42E R43E
 $\frac{1}{4}$
S 12 | S 7
- 1971
- set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
- From this cor., U.S.C. and G.S. triangulation station "STONE," monumented with a standard brass tablet set in concrete, bears N. $80^{\circ} 57'$ E., 16.72 chs. dist.
- 41.80 Fence, parallel to highway.
- 42.10 Power line, parallel to highway.
- 45.10 East-bound lane, Interstate Highway No. 80, bears S. $44\frac{1}{4}^{\circ}$ E. and N. $44\frac{1}{4}^{\circ}$ W.
- 50.20 West-bound lane, Interstate Highway No. 80, bears S. $44\frac{1}{4}^{\circ}$ E. and N. $44\frac{1}{4}^{\circ}$ W.
- 54.50 Fence, parallel to highway.
- 79.98 The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of T. 35 N., R. 43 E., executed under Group No. 472 in 1970.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey Executed by
U. S. Deputy Surveyors A. J. Hatch and J. H. Eaton
in 1869.

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.

N. $1^{\circ} 27'$ W., bet. secs. 35 and 36.