

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 39 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH A PORTION OF RANGE 39 EAST,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
W. D. Minckler, U. S. Deputy Surveyor
in 1881

The standard cor. of secs. 33 and 34, monumented with a
basalt stone, 10x10x12 ins., plainly mkd. SC and 3
grooves on the E. face and 3 grooves on the W. face and
firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins.
in the ground to bedrock and in a mound of stone, 4 ft.
base to top, with brass cap mkd.

SC
T46N R39E
S 33 | S 34

1972

bury the original corner stone alongside the iron post.

S. 89° 57' W., along the S. bdy. of sec. 33.

Over mountainous land, through sagebrush; asc. slightly
over a SE. slope.

1.40 Spur, slopes S.; desc. 280 ft. over a SW. slope.

12.00 Ravine, drains SSE.; asc. 280 ft. over an E. slope.

26.70 Ridge, bears NNE. and SSW.; desc. 210 ft. over a
W. slope.

39.82 The standard ¼ sec. cor. of sec. 33, monumented with a
basalt stone, 8x10x16 ins., plainly mkd. ¼ on the W.
face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

SC
T46N R39E
¼ S 33

1972

bury the original corner stone alongside the iron post
and raise a mound of stone, 3½ ft. base, 2½ ft. high,
N. of cor.