

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 40 E., MDM, NEVADA

CHAINS
82.22

Intersect the Ninth Standard Parallel North.

Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T46N R40E
S 35
S 2 | S 1
C C
T45N R40E

1972

raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.

From this corner the standard cor. of secs. 35 and 36, bears N. 89° 54' E., 2.45 chs. dist.

The point for the N. ¼ sec. cor. of sec. 1 is on the Ninth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 1.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

¼ S 1
T45N R40E

1972

From this corner the standard ¼ sec. cor. of sec. 36, bears N. 89° 59' E., 2.52 chs. dist.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 3 ft. base to top, with brass cap mkd.

T45N R40E
S 34 | S 35
S 3 | S 2
T44N

1963

N. 0° 16' E., bet. secs. 34 and 35.

Over rolling land, through sagebrush; desc. 110 ft. over a W. slope, changing to a NW. slope.