

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 40 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

T46N R40E
S 34
S 3 | S 2
C C
T45N R40E

1972

From this corner the standard cor. of secs. 34 and 35, bears N. 89° 53' E., 2.55 chs. dist.

The point for the N. ¼ sec. cor. of sec. 2 is on the Ninth Standard Parallel North and at midpoint in departure on the N. bdy. of sec. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground and in a collar of stone, with brass cap mkd.

¼ S 2
T45N R40E

1972

raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.

From this corner the standard ¼ sec. cor. of sec. 35, bears N. 89° 43' E., 2.46 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 4 ft. base to top, with brass cap mkd.

T45N R40E
S 33 | S 34
S 4 | S 3
T44N

1967

N. 0° 51' W., bet. secs. 33 and 34.

Over rolling land, through sagebrush; asc. 180 ft. over a W. slope, changing to a SW. slope.

40.38

Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner.