

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 40 E., MDM, NEVADA

CHAINS	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd.</p> <p style="text-align: center;">T45N R40E S 32 S 33 S 5 S 4 T44N</p> <p style="text-align: center;">1967</p> <p>N. 1° 53' E., bet. secs. 32 and 33.</p> <p>Over rolling land, through sagebrush; asc. 100 ft. over a S. slope.</p>
29.50	<p>Fence, on top of ascent bears E. and W.; desc. 110 ft. over a N. slope.</p>
40.36	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance falls in Martin Creek, 50 lks. wide, 4 ft. deep, course ESE., where corner cannot be perpetuated safely; there is no remaining evidence of the original corner.</p>
40.76	<p>Point selected for the witness ¼ sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R40E ¼ S 32 S 33 W C</p> <p style="text-align: center;">1972</p> <p>raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.</p> <p>Ascend 130 ft. over a S. slope.</p>
41.50	<p>Fence, bears NNE. and SSW.</p>
60.54	<p>Point for the N. 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R40E N 1/16 S 32 S 33</p> <p style="text-align: center;">1972</p>