

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 40 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T45N R40E
S 4
¼ S 9

1972

raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of cor.

Descend 190 ft. over a W. slope.

49.00 Creek, 10 lks. wide, 1 ft. deep, course S.; asc. 250 ft. over an E. slope.

63.20 Spur, slopes SSE.; desc. 50 ft. over a SW. slope.

72.90 Ravine, drains SE.; asc. 160 ft. over a NE. slope.

81.48 The cor. of secs. 4, 5, 8 and 9.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd.

T45N R40E
S 31 | S 32
S 6 | S 5
T44N

1967

N. 1° 17' E., bet. secs. 31 and 32.

Over rolling land, through sagebrush; asc. 40 ft. over a S. slope.

4.10 Spur, slopes SE.; desc. 30 ft. over a NE. slope.

18.30 Draw, drains ESE.; asc. 110 ft. over a SE. slope.

40.04 Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.

T45N R40E
¼
S 31 | S 32

1972