## DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 3 N., R. 52 E., MDM, NEVADA

	T. 3 N., R. 52 E., MDM, NEVADA
CHAINS	
	T3N R52E R53E S 1 S 6 S 12 S 7
	1972
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 18' E., bet. secs. 1 and 6.
	Over nearly level land, through budsage and shadscale.
17.90	Ditch, 5 lks. wide, 1 ft. deep, drains N. 70° E.
40.26	Point for the 4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to underlying rock and in a collar of stone, with brass cap mkd.
	T3N R52E R53E <sup>1</sup> 4
	s 1 s 6
	1972
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
47.40	Trail road, bears E. and W.
50.20	Gravel road, bears N. 78° E. and S. 78° W.
80.62	The cor. of Tps. 3 and 4 N., Rs. 52 and 53 E., monumented with a granite stone, $5x4x4$ ins., mkd. with 6 grooves on the N., E. and S. faces and firmly set in a mound of stone, with a steel fence post alongside.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4N R52E R53E S 36 S 31 S 1 S 6 T3N
	1972
	bury the original corner stone and reset the steel fence post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
1	