

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 3 N., R. 52 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 3 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
M. F. Reilly and T. A. Magee, U. S. Deputy Surveyors,
in 1881,
and Retracement and Resurvey Executed by F. T. Roberts,
U. S. Deputy Surveyor,
in 1909.

The corners along this boundary were established as
common corners but will now function as corners for
T. 3 N., R. 52 E. only.

From the cor. of Tps. 2, 2 $\frac{1}{2}$ and 3 N., Rs. 52 and 53 E.

N. 89° 57' W., along the S. bdy. of sec. 36.

Over nearly level land, through budsage and shadscale.

40.33 The S. $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a lava
stone, 8x6x5 ins., mkd. $\frac{1}{4}$ on the N. face and firmly set
in a mound of stone, with a steel fence post alongside.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 2 $\frac{1}{4}$ ins.
in the ground, with brass cap mkd.

T3N R52E
 $\frac{1}{4}$ S 36

1972

bury the original corner stone and reset the steel fence
post alongside the iron post and raise a mound of stone,
3 ft. base, 2 ft. high, N. of cor.

S. 89° 39' W., beginning new measurement.

Over nearly level land, through budsage and shadscale.

10.10 State Highway No. 25, bears S. 5° E. and N. 5° W.

20.90 Trail road, bears NE. and SW.

40.10 The cor. of secs. 35 and 36, monumented with a lava
stone, 10x8x6 ins., mkd. with 1 groove on the E. face
and 5 grooves on the W. face and firmly set 5 ins. in
the ground, with a mound of stone W.

At the corner point