DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 4 N., R. 54 E., MDM, NEVADA.

		1. 4 N., R. 34 E., FIDT, NEVADA.
	CHAINS	
	39.40	Trail road, bears S. 60° E. and N. 60° W.
	40.38	The cor. of secs. 5, 6, 31 and 32, monumented with a sandstone, 4x4x4 ins., mkd. with 5 grooves on the E. face and 1 groove on the W. face, firmly set in a mound of stone.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	•	T4N R54E S 31 S 32 S 6 S 5 T3N
j		1972
		bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
		S. 89° 48' W., bet. secs. 6 and 31.
		Descend over a gradual NW. slope, through budsage.
	40.36	The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a lava stone, $7x5x3$ ins., mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone.
		At the corner point
		Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T4N R54E
		S 31 S 6
		T3N
		1972
		bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
		S. 89° 46' W., beginning new measurement.
	40.27	The cor. of Tps. 3 and 4 N., Rs. 53 and 54 E., monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner.
		At the corner point