

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 4 N., R. 54 E., MDM, NEVADA.

CHAINS										
80.80	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T4N</td><td>R54E</td></tr> <tr><td>S 26</td><td> S 25</td></tr> <tr><td>S 35</td><td> S 36</td></tr> </table> <p>1972</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	T4N	R54E	S 26	S 25	S 35	S 36			
T4N	R54E									
S 26	S 25									
S 35	S 36									
	<p>The cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with a porphyry stone, 8x6x2 ins., mkd. with 5 grooves on the N. face and 1 groove on the S. face, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T4N</td><td>T4N</td></tr> <tr><td>R54E</td><td>R55E</td></tr> <tr><td>S 25</td><td> S 30</td></tr> <tr><td>S 36</td><td> </td></tr> </table> <p>1972</p> </div> <p>bury the original corner stone and deposit broken glass alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 89° 57' W., bet. secs. 25 and 36.</p> <p>Over nearly level land, through budsage.</p>	T4N	T4N	R54E	R55E	S 25	S 30	S 36		
T4N	T4N									
R54E	R55E									
S 25	S 30									
S 36										
0.30	Wash, 20 lks. wide, 1 ft. deep, drains N.									
3.50	Wash, 15 lks. wide, 2 ft. deep, drains N.									
8.40	Wash, 10 lks. wide, 3 ft. deep, drains N.									
9.30	Graded road, bears N. 50° E. and S. 50° W.									
33.70	Wash, 10 lks. wide, 2 ft. deep, drains N. 10° W.									
39.91	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>									