

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 12 N., R. 62 E., MDM, NEVADA

CHAINS	
	<p>The cor. of Tps. 11 and 12 N., Rs. 62 and 63 E., monumented with the original limestone, 12x10x8 ins., plainly mkd. with 6 notches on the N., S., E. and W. edges, firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R62E R63E S 36 S 31 S 1 S 6 T11N</p> </div> <p>1972</p> <p>bury the corner stone alongside the iron post.</p> <p>S. 89° 44' W., bet. secs. 1 and 36.</p> <p>Over mountainous land, through scattered sagebrush and greasewood, medium juniper and pinon; desc. 440 ft. over W. slope.</p>
29.00	Wash, 20 lks. wide, 2 ft. deep, drains SW.; desc. 40 ft. over rolling W. slope.
39.69	<p>Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R62E S 36 ¼ — S 1 T11N</p> </div> <p>1972</p> <p>Descend 250 ft. over rolling W. slope to the sec. cor.</p>
66.40	Wash, 20 lks. wide, 1 ft. deep, drains N.
67.80	Trail road, bears NW. and SE.
79.38	<p>The cor. of secs. 1, 2, 35 and 36, monumented with the original limestone, 12x10x10 ins., plainly mkd. with 1 notch on the E. edge and 5 notches on the W. edge, firmly set in a mound of stone.</p> <p>At the corner point</p>