

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 62 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T13N R62E S 19 ¼ ——— S 30</p> <p style="text-align: center;">1972</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
50.60	Trail road, bears NNW. and SSE.
79.13	<p>The cor. of secs. 19 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T13N T13N R61E R62E S 24 S 19 S 30</p> <p style="text-align: center;">1925</p>
40.16	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 15' E., bet. secs. 19 and 20.</p> <p>Over nearly level land, through scattered sagebrush and greasewood.</p> <p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T13N R62E ¼ S 19 S 20</p> <p style="text-align: center;">1972</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
53.10	Trail road, bears E. and W.
61.40	Wash, 10 lks. wide, 1 ft. deep, drains SSW.
80.32	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>