

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 13 N., R. 62 E., MDM, NEVADA

CHAINS	
50.00	Wash, 10 lks. wide, 1 ft. deep, drains S.
79.18	<p>The cor. of secs. 18 and 19, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set and exposed 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">           T13N T13N            R61E R62E            S 13   S 18                    S 19            1925         </p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 10' W., bet. secs. 17 and 18.</p> <p>Over nearly level land, through scattered sagebrush and greasewood.</p>
5.50	Wash, 10 lks. wide, 1 ft. deep, drains SW.
24.00	Wash, 20 lks. wide, 2 ft. deep, drains SW.
40.16	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">           T13N R62E                  <math>\frac{1}{4}</math>            S 18   S 17            1972         </p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
80.32	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">           T13N R62E            S 7   S 8            S 18   S 17            1972         </p>
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89° 25' W., bet. secs. 8 and 17.</p>