

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 62 E., MDM, NEVADA

CHAINS

T45N R62E

$$\begin{array}{c} \frac{1}{4} \\ S \ 5 | S \ 4 \end{array}$$

1972

Along rolling W. slope.

54.57 Intersect the Ninth Standard Parallel North.

The closing cor. of secs. 4 and 5, monumented with a basalt stone, 15x6x4 ins., mkd. with 4 grooves on the E. face, 2 grooves on the W. face, 6 grooves and CC on the S. face, with a scattered mound of stone S. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T46N R62E

$$\begin{array}{c} S \ 32 \\ \hline S \ 5 | S \ 4 \\ C \ C \end{array}$$

T45N R62E

1972

bury the original corner stone and set a steel fence post, 6 ft. long, 16 ins. in the ground, alongside the iron post.

From this corner, the standard corner of secs. 32 and 33, T. 46 N., R. 62 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of the Ninth Standard Parallel North, through a portion of Range 62 East, executed under this same group, bears S. 89° 58' E., 15.91 chs. dist.

The cor. of secs. 29, 30, 31 and 32, monumented with a basalt stone, 18x10x6 ins., mkd. with 5 notches on the E. edge and 1 notch on the S. edge, firmly set in the ground, with a scattered mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T45N R62E

$$\begin{array}{c} S \ 30 | S \ 29 \\ S \ 31 | S \ 32 \end{array}$$

1972

bury the original corner stone alongside the iron post.