

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 62 E., MDM, NEVADA

CHAINS	
	Descend 400 ft. over ledgy W. slope, changing to rolling N. slope.
39.26	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of a portion of the E. bdy., T. 45 N., R. 62 E., executed under this same group.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0° 20' W., bet. secs. 29 and 30.
	Over rolling land, through medium sagebrush; along rolling E. slope.
10.90	Trail road, bears NE. and SW.
39.97	The ¼ sec. cor. of secs. 29 and 30, monumented with a basalt stone, 24x8x3 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T45N R62E ¼ S 30 S 29</p>
	1972
	reset the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 14' E., beginning new measurement.
	Along rolling E. slope.
29.50	Trail road, bears NW. and SE.
35.40	Trail road, bears NW. and SE.
40.00	The cor. of secs. 19, 20, 29 and 30, monumented with a basalt stone, 16x12x3 ins., mkd. with 5 notches on the E. edge and 2 notches on the S. edge, firmly set in the ground, with a scattered mound of stone W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 2 ft. base to top, with brass cap mkd.