

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 62 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X), and in a mound of stone, 7 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R62E W 1/16 $\frac{S\ 17}{S\ 20}$</p> <p style="text-align: center;">1972</p> <p>Ascend 50 ft. over broken ledges.</p>
62.00	N. rim of canyon, bears NE. and SW.; asc. 130 ft. over E. slope.
82.20	The cor. of secs. 17, 18, 19 and 20.
	<p>N. 89° 58' W., bet. secs. 18 and 19.</p> <p>Over rolling land, through medium sagebrush; asc. 40 ft. over E. slope.</p>
8.00	Ridge, bears N. and S.; desc. gradually over W. slope.
25.80	Top of ledge, 200 ft. high, faces SW.; desc. 450 ft. over SW. slope.
39.65	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R62E $\frac{1}{4} \frac{S\ 18}{S\ 19}$</p> <p style="text-align: center;">1972</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor., and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Descend 50 ft. over SW. slope.</p>
41.70	Draw, drains S.; asc. 50 ft. over E. slope.
64.10	Telephone line, bears N. and S.; desc. 50 ft. over gently rolling W. slope.
74.80	Bladed road, bears WNW. and ESE., soon E.
79.30	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of a portion of the E. bdy. of T. 45 N., R. 62 E., executed under this same group.