

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 62 E., MDM, NEVADA

CHAINS	
	N. 0° 24' E., bet. secs. 5 and 6.
	Over gently rolling land, through medium sagebrush; desc. gradually along E. slope of broad ridge.
20.02	Point for the S. 1/16 sec. cor. of secs. 5 and 6, at proportionate distance.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T45N R62E S 1/16 S 6 S 5</p>
	1972
40.04	The ¼ sec. cor. of secs. 5 and 6, monumented with a basalt stone, 12x8x2 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T45N R62E ¼ S 6 S 5</p>
	1972
	bury the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 05' W., beginning new measurement.
	Descend gradually.
14.67	Intersect the Ninth Standard Parallel North.
	The closing cor. of secs. 5 and 6, monumented with a basalt stone, 16x12x9 ins., mkd. with 5 grooves on the E. face, 1 groove on the W. face and 6 grooves and CC on the S. face, firmly set in the ground, with a mound of stone S. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.