

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 62 EAST, MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S C T46N R62E <u>S 31   S 32</u></p> <p style="text-align: center;">1972</p> <p>bury the original corner stone alongside the iron post.</p>
	<p>N. 89° 54' W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, through medium sagebrush; asc. 50 ft. over E. slope.</p>
16.17	<p>The closing cor. of secs. 5 and 6, T. 45 N., R. 62 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of a portion of the subdivisional lines of T. 45 N., R. 62 E., of this same group.</p> <p>Ascend 20 ft. over E. slope.</p>
24.00	<p>Ridge, bears N. and S.; desc. 100 ft. over W. slope.</p>
40.11	<p>The standard ¼ sec. cor. of sec. 31, monumented with a basalt stone, 14x8x6 ins., mkd. SC ¼ on the N. face, firmly set in the ground, with a scattered mound of stone N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S C T46N R62E <u>¼ S 31</u></p> <p style="text-align: center;">1972</p> <p>bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>
	<p>N. 89° 52' W., beginning new measurement.</p>
	<p>Descend 40 ft. over W. slope.</p>
8.00	<p>Bottom of descent; thence over nearly level land.</p>
37.80	<p>Graded road, bears N. and S.</p>