

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,  
THROUGH A PORTION OF RANGE 62 EAST, MDM, NEVADA

<p>CHAINS 40.06</p>	<p>The standard cor. of Tps. 46 N., Rs. 61 and 62 E., monumented with a basalt stone, 17x12x8 ins., mkd. with 6 grooves on the N., E., and W. faces and SC on the N. face, firmly set in the ground, with a scattered mound of stone N. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T46N R61E R62E S C <u>S 36   S 31</u></p> <p style="text-align: center;">1972</p> <p>bury the original corner stone alongside the iron post and set a steel fence post, 6 ft. long, alongside the iron post.</p>	
	<p>DEPENDENT RESURVEY OF THE BOUNDARIES OF SECTION 32, T. 46 N., R. 62 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p style="text-align: center;">Reestablishment of the Survey Executed by U. S. Deputy Surveyor H. B. Maxson in 1899</p> <hr style="width: 20%; margin: auto;"/> <p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 1° 21' W., bet. secs. 32 and 33.</p> <p>Over rolling land, through medium sagebrush; asc. 170 ft. along broken W. slope.</p> <p>21.40 Spur, projects W.; desc. 130 ft. along rolling W. slope.</p> <p>39.70 The ¼ sec. cor. of secs. 32 and 33, monumented with a basalt stone, 16x8x5 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	