

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 32 N., R. 34 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T33N R34E
S 31 | S 32
S 6 | S 5
T32N

1972

reset the redwood post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 32 N., R. 34 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of a Portion of the Survey Executed by
E. H. Dyer, U. S. Deputy Surveyor,
in 1864,
and a Portion of the Survey and Resurvey Executed by
H. B. Maxson, U. S. Deputy Surveyor,
in 1893,
and a Portion of the Resurvey Executed by
T. A. Haigh, U. S. Surveyor and
A. T. Harris, U. S. Transitman,
in 1913-1914.

The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set and exposed 10 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd.

T32N R34E
S 14 | S 13
S 23 | S 24

1913

N. $7^{\circ} 10'$ E., bet. secs. 13 and 14.

Over rolling land.

43.88

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a mound of stone. This point is so near T. A. Haigh and A. T. Harris' record position in relation to their 1913-1914 iron posts one-half mile north and south that it is accepted as the corner point.

At the corner point