

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 32 N., R. 34 E., MDM, NEVADA

<p>CHAINS 43.88</p>	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R34E <math>\frac{1}{4}</math> S 11   S 12</p> <p style="text-align: center;">1972</p> <p>set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Over nearly level land; desc. 40 ft. over N. slope.</p>
<p>87.76</p>	<p>The cor. of secs. 1, 2, 11 and 12, monumented with the remains of the original willow post, loosely set in a mound of earth.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R34E S 2   S 1 S 11   S 12</p> <p style="text-align: center;">1972</p> <p>bury the remains of the willow post and set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p>
<p>39.57</p>	<p>From the cor. of secs. 1, 1, 12 and 12, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set and exposed 6 ins. above ground, with a steel fence post firmly set alongside, a mound of stone W. of cor., with brass cap mkd.</p> <p style="text-align: center;">T32N R34E R34<math>\frac{1}{2}</math>E S 1   S 1 S 12   S 12</p> <p style="text-align: center;">1967</p> <p>S. 89° 15' W., bet. secs. 1 and 12.</p> <p>Over nearly level land, through shadscale and greasewood.</p>