

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 N., R. 18 E., MDM, NEVADA

<p>CHAINS 83.78</p>	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented under Group No. 35, California, with an iron post, 2 ins. diam., firmly set in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T31N R17E R18E <u>S 13 S 18</u> <u>S 24 S 19</u></p> <p style="text-align: center;">1918</p> <p>This corner will now refer to secs. 13 and 18 only and I remark the brass cap to read:</p> <p style="text-align: center;">T31N R17E R18E <u>S 13 S 18</u></p> <p style="text-align: center;">1972 1918</p>
<p>7.00</p> <p>22.00</p> <p>39.82</p>	<p>From the SE. cor. of sec. 15.</p> <p>N. 0° 19' W., along the E. bdy. of sec. 15.</p> <p>Over mountainous land, covered with scattered sagebrush; asc. 60 ft. over SE. slope.</p> <p>Spur, slopes WSW.; desc. 180 ft. over NW. slope.</p> <p>Draw, drains SW.; asc. 270 ft. over SE. slope.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a scoria stone, 8x6x4 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on the W. face. This corner will now refer to sec. 15 only.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T31N R18E $\frac{1}{4}$ S 15 </p> <p style="text-align: center;">1972</p> <p>deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 16' W., beginning new measurement.</p> <p>Over mountainous land; asc. 20 ft. over SE. slope.</p>