

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 31 N., R. 18 E., MDM, NEVADA

CHAINS	
	S. 89° 13' W., bet. secs. 7 and 18.
	Over mountainous land, covered with sagebrush; desc. 60 ft. over NW. slope.
12.70	Rush Creek, 20 lks. wide, 1 ft. deep, course N.
15.30	Trail road, bears SSE. and NNW.; asc. 210 ft. over NE. slope.
33.00	Slope changes to N.; asc. 130 ft. along N. slope.
42.28	Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	$\begin{array}{r} \text{T31N R18E} \\ \text{S } 7 \\ \hline \frac{1}{4} \text{ S } 18 \end{array}$
	1972
	set a steel fence post, 6 ft. long, alongside the iron post.
	Ascend 50 ft. along N. slope.
48.00	Smoke Creek Road, bears N. 70° E. and S. 20° W. on curve; asc. 330 ft. over E. slope.
65.60	Mesa edge, bears NNE. and SSW.; across Mesa.
73.60	Mesa edge, bears N. and S.; desc. 230 ft. over W. slope.
84.03	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with a scoria stone, 24x18x16 ins., firmly set in the ground, mkd. with 4 notches on the S. edge and 2 notches on the N. edge, with a mound of stone W.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\begin{array}{r} \text{T31N} \\ \text{R17E R18E} \\ \text{S } 12 \mid \text{S } 7 \\ \text{S } 13 \mid \text{S } 18 \end{array}$
	1972
	deposit the original cornerstone and set a steel fence post, 6 ft. long, alongside the iron post.