DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 32 N., R. 18 E., MDM, NEVADA

T. 32 N., R. 18 E., MDM, NEVADA		
	CHAINS	T32N R18E
		<u>s 31  s 32</u>
		S 6 S 5 T31N
		1972
		deposit the original cornerstone and set a steel fence
		post, 6 ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.
		N. 89° 38' W., bet. secs. 6 and 31.
		Over nearly level land, covered with sagebrush.
	10.70	Bladed road, bears S. 30° E. and N. 30° W.
	12.10	Fence, bears S. 29½° E. and N. 29½° W.
	28.40	Fence, bears N. 55 3/4° E. and S. 55 3/4° W.
	38.90	Fence, bears S. 44° E. and N. 44° W.
	39.96	Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T32N R18E
		1 S 31 S 6
		T3lN
		1972
		set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
		Continue over nearly level land.
	46.90	Ditch, 20 lks. wide, 4 ft. deep, course SSE.
	57•90	Fence, bears S. 30½°E. and N. 30½° W.
	62.30	Smoke Creek, 20 lks. wide, 1 ft. deep, course SSE., leave bottom land, bears SSE. and NNW.; asc. 230 ft. over E. slope.
	79•30	The cor. of Tps. 31 and 32 N., Rs. 17 and 18 E., monumented with a basalt stone, 18x14x12 ins., firmly set in a mound of stone, mkd. with 6 notches on the N., S., E. and W. edges, with a mound of stone S.
		At the corner point
		•