

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 23 N., R. 52 E., MDM, NEVADA

CHAINS

80.40

The cor. of Tps. 23 and 24 N., Rs. 52 and 53 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, S. of cor., with brass cap mkd. as described in the field notes of the resurvey of the east boundary of T. 24 N., R. 52 E., executed concurrently under this same Group.

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 23 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. L. Bridges and J. H. Eaton, U. S. Deputy Surveyors,
in 1879,
and a Portion of the Survey Executed by
W. T. Moran, U. S. Deputy Surveyor,
in 1893

From the cor. of Tps. 22 and 23 N., Rs. 52 and 53 E.

N. 89° 00' W., bet. secs. 1 and 36.

Over nearly level land, through sagebrush.

9.60

Wash, drains N.

10.00

Trail road, bears SE. and NW.

40.11

Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R52E
S 36
¼ S 1
T22N

1972

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

61.90

Power and telephone line, bears SSE. and NNW.

62.30

Gravel road, bears SSE. and NNW.; over gently rolling land, through sagebrush; asc. 100 ft. over a gradual NE. slope.

80.22

The cor. of secs. 1, 2, 35 and 36, monumented with a steel fence post firmly set in a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original corner. This corner was tied in by Tellurometer traverse under Group No. 389 and shown on Protraction Diagram No. 164.