

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 23 N., R. 52 E., MDM, NEVADA

CHAINS	
46.00	Spur, slopes S.; desc. 50 ft. over a broken SW. slope.
63.60	Trail road, bears SE. and NW.
65.00	Draw, drains SE.; asc. 160 ft. over an E. slope.
83.00	Spur, slopes SE.; desc. 20 ft. over a SW. slope.
85.80	Draw, drains S.
86.32	Intersect the E. bdy. of sec. 36, T. 23 N., R. 51 E.
	The closing corner of secs. 6 and 31, monumented with the original slate stone, 16x4x3 ins., plainly mkd. CC on the E. face and firmly set in a mound of stone. This corner now refers to sec. 31 only.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<div>T23N T23N R52E R51E S 31CC S 36 </div>
	1972
	bury the marked stone alongside the iron post.
	From this corner, the cor. of secs. 25 and 36, T. 23 N., R. 51 E., bears N. 0° 20' W., 0.84 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 3 ft. base to top, with brass cap mkd. as described in the field notes of the resurvey of the E. bdy. of T. 23 N., R. 51 E., executed concurrently under this same group.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 23 N., R. 52 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by E. L. Bridges and J. H. Eaton, U.S. Deputy Surveyors, in 1879
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
	N. 0° 17' E., bet. secs. 35 and 36.
	Over gently rolling land, through sagebrush; desc. 40 ft. over a NE. slope.
8.00	Bottom of descent; over a broken E. slope.