

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 52 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T23N R52E $\frac{1}{4}$ $\frac{S \ 2}{S \ 11}$</p> <p style="text-align: center;">1973</p> <p>bury broken glass alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 1° 19' E., bet. secs. 1 and 2.</p> <p>Over nearly level land, through sagebrush.</p>
1.40	Fence, bears E. and W.
40.07	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with an unmarked wooden post, 2x2x24 ins. long and loosely set in a mound of earth. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T23N R52E $\frac{1}{4}$ S 2 S 1</p> <p style="text-align: center;">1973</p> <p>reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 1° 11' E., beginning new measurement.</p> <p>Over nearly level land, through sagebrush.</p>
29.60	Gravel road, bears NNE. and SSW.
40.14	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with a steel fence post alongside and a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south bdy. of T. 24 N., R. 52 E., executed concurrently under this same group.</p>
	<p>From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp.</p> <p>N. 1° 00' E., along the E. bdy. of sec. 31.</p>