DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,

 	T. 23 N., R. 52 E., MDM, NEVADA
CHAINS 81.70	Dismantled railroad, bears N. and S.
82.00	Henderson Creek, 40 lks. wide, 10 ft. deep, course N., changing to E., changing to NNE.
90.30	Vinini Creek, 20 lks. wide, 2 ft. deep, course N.; asc. 60 ft. over an E. slope.
125.37	Intersect the E. bdy. of sec. 13, T. 23 N., R. 51 E.
	The closing corner of secs. 18 and 19, monumented with the original basalt stone, 10x8x5 ins., plainly mkd. CC on the E. face, 3 notches on the N. edge and 3 notches on the S. edge, firmly set 5 ins. in the ground.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T23N R51E R52E S 13 S 19 C
	1972
	bury the marked stone alongside the iron post and raise

bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this corner, the cor. of secs. 12 and 13, T. 23 N., R. 51 E., bears N. 0° 16' W., 0.54 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. as described in the field notes of the resurvey of the E. bdy. of T. 23 N., R. 51 E., executed concurrently under this same group.

The point for the W. 4 sec. cor. of sec. 19 is at mid-point and on the W. bdy. of the Tp.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

|T23N |R52E | ¼ |S 19

1973

From this corner, the ½ sec. cor. of sec. 13, T. 23 N., R. 51 E., bears N. 0° 40' W., 0.635 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd. as described in the field notes of the resurvey of the E. bdy. T. 23 N., R. 51 E., executed concurrently under this same group.