DEPENDENT	RESURVEY	OF A	PORTION	OF THE	SUBDIVISIONAL	LINES,
	m /	TI CC	ם בס ד	יו די די	A CT A T FETTE T	•

	T. 23 N., R. 52 E., MDM, NEVADA					
CHAINS	WEST, bet. secs. 7 and 18.					
	Over rolling land, through juniper, pinon and sagebrush; over a NE. slope.					
10.00	Spur, slopes NW.; desc. 100 ft. over a W. slope.					
40.28	Point for the k sec. cor. of secs. 7 and 18, at porportionate distance; there is no remaining evidence of the original corner.					
	Set an iron post, 28 ins. long, 2½ ins. diam., 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	X				
	T23N R52E					
	1 ₄ S 7 S 18					
	1972					
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.					
	Descend 60 ft. over a W. slope.					
56.30	Wash, 20 lks. wide, 3 ft. deep, drains NNW.; desc. 40 ft. over a W. slope.					
67.90	State Highway No. 51, bears N. 4° W. and S. 4° E.					
75.00	Dismantled railroad, bears N. and S.					
79.90	Henderson Creek, course N., irregularly; asc. 100 ft. over an E. slope.					
117.50	Spur, slopes N.; desc. 40 ft. over a W. slope.					
123.00	Draw, drains N.; asc. over an E. slope.					
125.37	Intersect the E. bdy. of sec. 12, T. 23 N., R. 51 E.					
	The closing corner of secs. 7 and 18, monumented with the original basalt stone, 12x9x9 ins., plainly mkd. CC on the E. face, 2 notches on the N. edge and 4 notches on the S. edge and firmly set 6 ins. in the ground, with a mound of stone W.					
	At the corner point					
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.					
	T23N R51E R52E S 12 S 7 C S 18 C					
	1972					