

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 51 E., MDM, NEVADA

CHAINS	
18.50	Wash, 10 lks. wide, 2 ft. deep, drains W.; over a W. slope.
33.80	Bladed road, bears E. and W.
34.20	Wash, 10 lks. wide, 2 ft. deep, drains W.; over a W. slope.
40.45	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with the original granite stone, 24x18x12 ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set 6 ins. the ground. This corner now refers to sec. 6 only.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T23N R52E $\frac{1}{4}$ S 6
	1972
	bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 1° 48' E., beginning new measurement.
	Over rolling land, through juniper and sagebrush; over a W. slope.
18.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.; over a W. slope.
35.02	Intersect the S. bdy. of sec. 31, T. 24 N., R. 52 E.
	The closing corner of secs. 5 and 6, monumented with the original granite stone, 12x12x6 ins., plainly mkd. CC on the S. face, 1 notch on the W. edge, 5 notches on the E. edge and firmly set 6 ins. in the ground, with a steel fence post alongside and a mound of stone S. This corner was tied in by Tellurometer traverse under Group No. 389 and shown on Protraction Diagram No. 164.
	At the corner point
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone, with brass cap mkd.