

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 24 N., R. 52 E., MDM, NEVADA

CHAINS		
	<p>N. 4° 05' E., beginning new measurement.</p> <p>Over nearly level land, through greasewood.</p> <p>19.60 Fence, bears S. 89° E. and N. 89° W.</p> <p>39.73 The cor. of secs. 1, 6, 7 and 12, monumented with a star drill, 26 ins. long, 1 in. diam., firmly set 18 ins. in the ground. This point is locally recognized as the corner position and is accepted as a careful and faithful determination of the original corner position by local survey using the rules of proportionate measurement.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T24N R52E R53E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1973</p> <p>insert the star drill inside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, the W. edge of a spring, bears N. 80° W., 7.30 chs. dist.</p>	
	<p>N. 4° 05' E., bet. secs. 1 and 6.</p> <p>Over nearly level land, through sagebrush and greasewood.</p> <p>27.70 Fence, bears N. 46° E. and S. 46° W.</p> <p>31.70 Gravel road, bears ENE. and WSW.; over gently rolling land, through sagebrush and greasewood; asc. 50 ft. over a SE. slope to the ¼ sec. cor.</p> <p>34.80 Ravine, drains SSE. changing to SE.</p> <p>39.75 The ¼ sec. cor. of secs. 1 and 6, monumented with an iron pipe, 16 ins. long, 1 in. diam., firmly set 10 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">¼ S 1 S 6</p> <p>This point is locally recognized as the corner position and is accepted a a careful and faithful determination of the original corner position by local survey using the rules of proportionate measurement.</p> <p>At the corner point</p>	