

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 24 N., R. 52 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T24N R52E
S 31 | S 32
S 5
T23N R52E

1972

bury the marked stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.

S. $88^{\circ} 53'$ W., along the S. bdy. of sec. 31.

Over gently rolling land, through juniper; desc. 120 ft. over a W. slope.

30.63 The closing cor. of secs. 5 and 6, T. 23 N., R. 52 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a collar of stone, with a steel fence post alongside, with brass cap mkd. as described in the field notes of the resurvey of the subdivisional lines of T. 23 N., R. 52 E., executed concurrently under this same Group.

Descend 30 ft. over a W. slope.

40.45 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with the original basalt stone, 18x16x12 ins., plainly mkd. $\frac{1}{4}$ on the N. face and firmly set in a mound of stone. This cor. now refers to sec. 31, T. 24 N., R. 52 E., only.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T24N R52E
 $\frac{1}{4}$ S 31

1972

bury the marked stone alongside the iron post.

S. $89^{\circ} 55'$ W., beginning new measurement.

Over gently rolling land, through sagebrush; desc. 40 ft. over a gradual W. slope.

5.00 Wash, 10 lks. wide, 2 ft. deep, drains NW.