

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 24 N., R. 53 E., MDM, NEVADA

CHAINS							
	<p>DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 24 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p>Reestablishment of the Survey Executed by O. A. Palmer, U. S. Deputy Surveyor, in 1870</p> <hr/> <p>Point for the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., at record bearing and distance from the cor. of secs. 5, 6, 31 and 32; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div><div>T25N R53E</div><div>S 32 S 33</div><div>S 5 S 4</div><div>T24N R53E</div></div> <p>1973</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor. WEST, bet. secs. 5 and 32.</p> <p>Over an alkali flat.</p> <tr><td>39.00</td><td>Leave alkali flat; enter greasewood, rabbitbrush and sagebrush.</td></tr> <tr><td>40.00</td><td><p>Point for the ¼ sec. cor. of secs. 5 and 32, at propor- tionate distance; there is no remaining evidence of the original corner.</p><p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p><div><div>T25N R53E</div><div>S 32</div><div>¼ S 5</div><div>T24N R53E</div></div><p>1973</p><p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p></td></tr> <tr><td>80.00</td><td><p>The cor. of secs. 5, 6, 31 and 32, monumented with the original squared cedar post, 1x2x12 ins. long, with illegible scribe marks visible, loosely set in a mound of earth, with an iron pipe, ½ in. diam., firmly set and exposed 6 ins. above ground alongside.</p><p>At the corner point</p><p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p></td></tr>	39.00	Leave alkali flat; enter greasewood, rabbitbrush and sagebrush.	40.00	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at propor- tionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div><div>T25N R53E</div><div>S 32</div><div>¼ S 5</div><div>T24N R53E</div></div> <p>1973</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	80.00	<p>The cor. of secs. 5, 6, 31 and 32, monumented with the original squared cedar post, 1x2x12 ins. long, with illegible scribe marks visible, loosely set in a mound of earth, with an iron pipe, ½ in. diam., firmly set and exposed 6 ins. above ground alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
39.00	Leave alkali flat; enter greasewood, rabbitbrush and sagebrush.						
40.00	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at propor- tionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div><div>T25N R53E</div><div>S 32</div><div>¼ S 5</div><div>T24N R53E</div></div> <p>1973</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>						
80.00	<p>The cor. of secs. 5, 6, 31 and 32, monumented with the original squared cedar post, 1x2x12 ins. long, with illegible scribe marks visible, loosely set in a mound of earth, with an iron pipe, ½ in. diam., firmly set and exposed 6 ins. above ground alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>						