

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 24 N., R. 53 E., MDM, NEVADA

CHAINS

This corner was tied in by tellurometer traverse under Group No. 389, and shown on protraction diagram No. 164.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 24 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
O. A. Palmer, U. S. Deputy Surveyor,  
in 1870  
and the Survey Executed by  
E. L. Bridges and J. H. Eaton, U. S. Deputy Surveyors,  
in 1879.

This boundary was originally surveyed and corner points monumented referring to both Tps. 23 and 24 N. Corners were reestablished that refer to surveyed areas only, with new corners at 40.00 ch. intervals in departure from the SE. Tp. cor. for the E. 3 miles referring to T. 24 N. only. A diligent search was made for the intervening corners of the original survey, but none were found.

The cor. of Tps. 23 and 24 N., Rs. 53 and 54 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with a steel fence post firmly set and exposed 4 ft. above ground, alongside the iron post, and a mound of stone, 4 ft. base, 3 ft. high, S. of cor., with brass cap mkd. as described in the field notes of T. 23 N., R. 54 E., executed concurrently under Group No. 504.

This cor. was tied in by tellurometer traverse under Group No. 389 and shown on protraction diagrams Nos. 164 and 165.

S. 88° 55' W., along the S. bdy. of sec. 36.

Over nearly level land, through shadscale, sagebrush and greasewood.

39.435 Point for the ¼ sec. cor. of sec. 1, T. 23 N., R. 53 E., only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.