

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 23 N., R. 53 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 23 N., R. 53 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by E. L. Bridges and J. H. Eaton, U.S. Deputy Surveyors in 1879</p> <hr/> <p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with a rebar, with metal tag mkd. L.S. 451 attached, with a wooden post, 3x3x72 ins. long, plainly mkd. with 6 grooves on the N. face and 5 grooves on the E. face, loosely set alongside. The rebar is set in a fence extending E. and W. This is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23N R53E S 31   S 32 S 6   S 5 T22N</p> <p>1973</p> </div> <p>reset the rebar and wooden post alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</p> <p>N. 1° 43' E., bet. secs. 31 and 32.</p> <p>Over nearly level land, through greasewood and sagebrush.</p> <p>27.90 Trail road, bears E. and W.</p> <p>40.15 Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23N R53E ¼ S 31   S 32</p> <p>1973</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>58.10 Trail road, bears NE. and SW.</p> <p>61.70 Trail road, bears ENE. and WSW.</p>