

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 23 N., R. 51 E., MDM, NEVADA

CHAINS	
4.70	Leave trail road, curves NE.
39.64	The W. $\frac{1}{4}$ sec. cor. of sec. 7, T. 23 N., R. 52 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, E. of cor., with brass cap mkd. as described in the field notes of the resurvey of the subdivisional lines of T. 23 N., R. 52 E., executed concurrently under this same group.
40.34	The $\frac{1}{4}$ sec. cor. of sec. 1, monumented with the original basalt stone, 12x10x8 ins., plainly mkd. $\frac{1}{4}$ on the W. face and firmly set 6 ins. in the ground, with a mound of stone W.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<div style="text-align: center;"> T23N R51E $\frac{1}{4}$ S 1 </div>
	1972
	bury the marked stone alongside the iron post.
	This corner is located on a low spur sloping NE.
	N. 0° 37' E., beginning new measurement.
	Over gently rolling land, through sagebrush.
11.60	Trail road, bears E. and W.
24.00	Spur, slopes NE; desc. 50 ft. over a NW. slope.
38.70	Frazier Creek, course E.
39.60	The closing corner of secs. 6 and 7, T. 23 N., R. 52 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, E. of cor., with brass cap mkd. as described in the field notes of the resurvey of the subdivisional lines of T. 23 N., R. 52 E., executed concurrently under this same group.
40.42	Point for the 80 $\frac{1}{16}$ sec. cor. of sec. 1, at proportionate distance.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.