

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 23 N., R. 51 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23N R51E
S 34 | S 35
S 3 | S 2
T22N

1972

bury the marked stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

S. 88° 47' W., bet. secs. 3 and 34.

Over mountainous land, through juniper and pinon; asc. 90 ft. over a S. slope.

- 9.00 Spur, slopes S.; desc. 40 ft. over a W. slope.
- 11.00 Ravine, drains S.; asc. over an E. slope.
- 13.50 Spur, slopes S.; desc. 30 ft. over a W. slope.
- 16.50 Ravine, drains S.; asc. 70 ft. over an E. slope.
- 21.00 Spur, slopes S.; desc. 160 ft. over a W. slope.
- 36.00 Ravine, drains SE.; asc. 50 ft. over a broken E. slope.
- 40.17 The ¼ sec. cor. of secs. 3 and 34, monumented with the original quartzite stone, 10x4x3 ins., plainly mkd. ¼ on the N. face and firmly set 6 ins. in the ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T23N R51E
S 34
¼ S 3
T22N

1972

bury the marked stone alongside the iron post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 51 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
W. T. Moran, U. S. Deputy Surveyor,
in 1893