

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 23 N., R. 51 E., MDM, NEVADA

CHAINS									
	<div>T23N R51E</div> <div>120 1/16</div> <div>S 2 S 1</div> <div>1973</div> <div>raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.</div> <tr><td>83.50</td><td>Trail road, bears NE. and SW.</td></tr> <tr><td>115.62</td><td><div>The closing corner of secs. 1 and 2, monumented with the original limestone, 24x12x10 ins., plainly mkd. CC on the S. face, 1 notch on the E. edge, 5 notches on the W. edge and firmly set 6 ins. in the ground. Add the marks AM and reset the stone, 8 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top.</div><div>The AM is located on the N. side of a low spur sloping E.</div><div>Descend over a N. slope.</div><tr><td>118.17</td><td><div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div><div>Point for the closing corner of secs. 1 and 2.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div></td></tr><tr><td></td><td><div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div></td></tr></td></tr>	83.50	Trail road, bears NE. and SW.	115.62	<div>The closing corner of secs. 1 and 2, monumented with the original limestone, 24x12x10 ins., plainly mkd. CC on the S. face, 1 notch on the E. edge, 5 notches on the W. edge and firmly set 6 ins. in the ground. Add the marks AM and reset the stone, 8 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top.</div> <div>The AM is located on the N. side of a low spur sloping E.</div> <div>Descend over a N. slope.</div> <tr><td>118.17</td><td><div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div><div>Point for the closing corner of secs. 1 and 2.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div></td></tr> <tr><td></td><td><div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div></td></tr>	118.17	<div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div> <div>Point for the closing corner of secs. 1 and 2.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div>		<div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div>
83.50	Trail road, bears NE. and SW.								
115.62	<div>The closing corner of secs. 1 and 2, monumented with the original limestone, 24x12x10 ins., plainly mkd. CC on the S. face, 1 notch on the E. edge, 5 notches on the W. edge and firmly set 6 ins. in the ground. Add the marks AM and reset the stone, 8 ins. in the ground to bedrock and in a mound of stone, 3½ ft. base to top.</div> <div>The AM is located on the N. side of a low spur sloping E.</div> <div>Descend over a N. slope.</div> <tr><td>118.17</td><td><div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div><div>Point for the closing corner of secs. 1 and 2.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div></td></tr> <tr><td></td><td><div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div><div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div><div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div></td></tr>	118.17	<div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div> <div>Point for the closing corner of secs. 1 and 2.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div>		<div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div>				
118.17	<div>Intersect the S. bdy. of sec. 35, T. 24 N., R. 51 E.</div> <div>Point for the closing corner of secs. 1 and 2.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>S 35</div><div>S 2 S 1</div><div>C C</div><div>T23N R51E</div><div>1973</div><div>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</div><div>From this corner, the cor. of secs. 34 and 35, T. 24 N., R. 51 E., bears N. 89° 30' W., 2.28 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above ground, with a mound of stone, 3 ft. base, 2 ft. high, N. of cor., with brass cap mkd. as described in the field notes of the resurvey of the south boundary of T. 24 N., R. 51 E., executed concurrently under this same group.</div></div>								
	<div>The point for the N. ¼ sec. cor. of sec. 1 is at midpoint and on the N. bdy. of the Tp.</div> <div>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</div> <div><div>T24N R51E</div><div>¼ S 1</div><div>T23N R51E</div><div>1973</div></div>								