

REESTABLISHMENT OF A PORTION
OF THE ORIGINAL MEANDER LINES,
T. 24 N., R. 23 E., MDM, NEVADA

CHAINS


REESTABLISHMENT OF A PORTION
OF THE ORIGINAL MEANDER LINES,
T. 24 N., R. 23 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
Winfred A. Pray, U. S. Transitman,
in 1916.

From the meander cor. of secs. 24 and 25, monumented
with an iron post, 1 in. diam., rusted off at ground
level, with brass cap laying alongside, mkd. as described
in the field notes of T. 24 N., R. 23 E., surveyed under
Group Nos. 33 and 47. Mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.




deposit the 1 in. iron post inverted, and broken glass
alongside the iron post and rebuild the mound of stone,
3 ft. base, 2 ft. high, W. of cor.

Thence with the adjusted original meanders of Winnemucca
Lake in sec. 24, describing a fixed and limiting boundary.

N. 35° 30' W., 7.41 chs. Point for the adjusted position
of Angle Point No. 1.

Set an iron post, 28 ins. long,
2½ ins. diam., 22 ins. in the
ground, with brass cap mkd.



raise a mound of stone, 3 ft.
base, 2 ft. high, S. of cor.

N. 66° 29' W., 11.31 chs. Point for the adjusted position
of Angle Point No. 2.