

REESTABLISHMENT OF A PORTION  
OF THE ORIGINAL MEANDER LINES,  
T. 24 N., R. 23 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, 2¼ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="893 470 1185 645"> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, SW. of cor.</p> <p>S. 86° 44' W., 17.17 chs. The meander cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., rusted off at ground level, with brass cap laying alongside, mkd. as described in the field notes of T. 24 N., R. 23 E., surveyed under group Nos. 33 and 47. Mound of stone S. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div data-bbox="746 1276 900 1384"> </div> <p>1972</p> <p>deposit the 1 in. iron post inverted, and broken glass alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, native grasses.</p>	
	<p>SURVEY AND COMPLETION SURVEY OF THE EAST BOUNDARY, T. 24 N., R. 23 E., MOUNT DIABLO MERIDIAN, NEVADA</p>	
	<p>From the meander cor. of secs. 25 and 30, monumented with a basalt stone, 24x16x12 ins., firmly set in the ground, and exposed 14 ins., mkd. T24NR23E on S. face, 30 on E. face, 25 on W. face, and MC on N. face, with a mound of stone S. This will also now function as an Angle Point.</p> <p>At the corner point</p>	