## SURVEY AND COMPLETION SURVEY OF THE EAST BOUNDARY, T. 24 N., R. 23 E., MDM, NEVADA

	T. 24 N., R. 23 E., MDM, NEVADA
CHAINS	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.
	T24N R24E S5A
	C C S 12 S 7
	R23E R24E T24N
	1976
	From this corner the SW. cor. of sec. 5A, on the median line of Winnemucca Lake, bears S. 84° 51' W., 14.89 chs. dist., monumented with an iron post, 2½ ins. in diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 24 N., R. 24 E., surveyed concurrently under this same group.
	NORTH, continue measurement, on a blank line across sec. 5A.
80.00	Point for the cor. of secs. 1, 6, 7 and 12.
	POINT NOT PERMANENTLY MONUMENTED.
	Land, nearly level. Soil, sandy clay loam. Undergrowth, native grasses.
	NORTH, on a blank line across sec. 5A.
	Over nearly level bottom land, covered with native grasses.
40.00	Point for the ½ sec. cor. of secs. 1 and 6.
	POINT NOT PERMANENTLY MONUMENTED.
	From this point the point for the E. % sec. cor. of sec. 1, on the E - W center line of sec. 1, bears WEST, 19.76 chs. dist.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T24N T24N R24E C C S 5A
	1976
67.76	Intersect the partitional line on the N. bdy. of sec. 5A.
	Point for the closing cor. of secs. 1 and 6.