

SURVEY AND COMPLETION SURVEY OF THE SUBDIVISIONAL LINES,
T. 24 N., R. 23 E., MDM, NEVADA

| | | |
|-------|--------|--|
| | CHAINS | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T24N R23E S 13 S 24 CC</div><div>S 23</div></div> <p>1972</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>From this corner the angle point in sec. 12, bears N. 24° 06' E., 95.19 chs. dist.</p> <p>Land, nearly level. Soil, sandy clay loam. Undergrowth, native grasses.</p> <hr/> <p>From the point for the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp. Point not permanently monumented, hereinbefore described.</p> <p>WEST, on a blank line, across sec. 5A.</p> <p>Over nearly level lake bottom, covered with native grasses.</p> |
| 16.16 | | <p>Intersect the median line on the W. bdy. of sec. 5A.</p> <p>Point for the closing cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div><div>T24N S 1 S 12 R23E</div><div>CC</div><div>T24N R24E S 5A</div></div> <p>1976</p> <p>From this corner the SW. cor. of sec. 5A, monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of T. 24 N., R. 24 E., surveyed concurrently under this same group, bears S. 5° 09' E., 14.86 chs. dist.</p> <p>WEST, continue measurement, bet. secs. 1 and 12.</p> |
| 40.00 | | <p>Point for the ¼ sec. cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div><div>T24N R23E S 1 S 12</div><div>¼</div></div> <p>1972</p> <p>set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> |