

DEPENDENT RESURVEY AND COMPLETION SURVEY  
OF A PORTION OF THE NORTH BOUNDARY  
T. 24 N., R. 24 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY AND COMPLETION SURVEY  
OF A PORTION OF THE NORTH BOUNDARY  
T. 24 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey Executed  
by U.S. Deputy Surveyor, T.K. Stewart in 1900.

The cor. of secs. 3, 4, 33 and 34, monumented with a  
granite stone, 12 x 8 x 5 ins., firmly set 6 ins. in the  
ground, mkd. with 3 notches on E. and W. edges.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T25N	R24E
S 33	S 34
S 4	S 3
T24N	

1972

deposit the original cornerstone and set a steel fence  
post, 6 ft. long alongside the iron post, and raise a  
mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of cor.

N.  $89^{\circ} 45'$  W., bet. secs. 4 and 33.

Over rolling land, covered with sagebrush and native  
grasses; desc. 170 ft. over W. slope to  $\frac{1}{4}$  cor.

- |       |   |
|-------|---|
| 2.50  | Wash, 20 lks. wide, 3 ft. deep, drains SW.  |
| 12.50 | Trail road, bears SE. and NW.   |
| 21.00 | Wash, 10 lks. wide, 3 ft. deep, drains WSW.   |
| 39.91 | The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented with a<br>well inbedded mound of stone, this point is harmoniously<br>related with other existing original corners and is<br>accepted as the best available evidence of the position<br>of the original corner. |

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T25N	R24E
$\frac{1}{4}$ S 33	
S 4	
T24N	

1972

raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, N. of  
cor.