DEPENDENT RESURVEY AND COMPLETION SURVEY OF A PORTION OF THE NORTH BOUNDARY T. 24 N., R. 24 E., MDM, NEVADA

	T. 24 N., R. 24 E., MDM, NEVADA	
CHAINS	WEST, on the N. bdy. of sec. 37, on a transit line describing the tangent.	
	Over nearly level land, enter Winnemucca Lake, edge bears NNW. and SSE.; over dry lake bed.	
23.63	Point for the ½ sec. cor. of sec. 37, determined at 120.00 chs. E. of the cor. of Tps. 24 and 25 N., R. 24 E., NORTH 0.1 lks. dist. from the tangent.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	え S 37 T24N R24E	
	1976	
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.	
63.63	Point for the cor. of secs. 6 and 37, determined at 80.00 chs. E. of the cor. of Tps. 24 and 25 N., R. 24 E., NORTH 0.5 lks. dist. from the tangent.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	S 6 S 37 T24N R24E	
	1976	
	set a steel fence post, 6 ft. long, alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.	
	Land, nearly level. Soil, sandy clay loam. Undergrowth, native grasses.	
	WEST, on the N. bdy. of sec. 6, on a transit line describing the tangent, which bears S. 89° 59.4' W.	
	Over nearly level lake bottom, covered with native grasses.	
40.00	Point for the 4 sec. cor. of sec. 6, determined at 40.00 chs. E. of the cor. of Tps. 24 and 25 N., R. 24 E., NORTH 1.7 lks. dist. from the tangent.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	14 S 6 T24N R24E	
	1976	
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.	