

DEPENDENT RESURVEY AND COMPLETION SURVEY
OF A PORTION OF THE NORTH BOUNDARY
T. 24 N., R. 24 E., MDM, NEVADA

CHAINS
80.00

Point for the cor. of Tps. 24 and 25 N., R. 24 E., determined North of the meander corner of secs. 25 and 30, on the W. bdy. of the Tp. and West of the meander corner of secs. 5 and 32, on the N. bdy. of the Tp., to an intersection. NORTH 2.7 lks. dist. from the tangent.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T25N		T25N
R23E		R24E
S 36		S 31
		S 6
		T24N

1972

set a steel fence post, 6 ft. long alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this cor. the cor. of Tps. 24 and 25 N., R. 23 E., bears SOUTH, 0.66 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above the ground, surveyed concurrently under this same group.

Land, nearly level.
Soil, sandy clay loam.
Undergrowth, native grass.

DEPENDENT RESURVEY AND COMPLETION SURVEY
OF A PORTION OF THE SUBDIVISIONAL LINES
T. 24 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of a Portion of the Survey
Executed by T. K. Stewart, in 1900.

The cor. of secs. 15, 16, 21 and 22, monumented with a basalt stone, 16 x 8 x 8 ins., firmly set in the ground, mkd. with 3 notches on S. and E. edges, with a mound of stone W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone 5 ft. base to top, with brass cap mkd.

T24N	R24E
S 16	S 15
S 21	S 22

1972

deposit the original cornerstone alongside the iron post.