

REESTABLISHMENT OF THE ORIGINAL MEANDER LINES
IN SECS. 5, 17 AND 19, T. 24 N., R. 24 E., MDM, NEVADA

CHAINS

REESTABLISHMENT OF THE ORIGINAL MEANDER LINES
IN SECTIONS 5, 17 AND 19, T. 24 N., R. 24 E.,
MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U.S. Deputy Surveyor, T. K. Stewart, in 1900.

From the meander cor. of secs. 5 and 32 on the N. bdy.
of sec. 5.

Thence with the adjusted original meanders of Winnemucca
Lake in sec. 5, describing a fixed and limiting boundary.

S. 7° 00' E., 9.01 chs. Point for the adjusted posi-
tion of Angle Point No. 1.

Set an iron post, 28 ins.
long, 2½ ins. diam., 22 ins.
in the ground, with brass cap
mkd.

AP 1 T24N
 R24E
 S 5

1976

Set a steel fence post, 6 ft.
long, alongside the iron post.

S. 14° 00' E., 16.03 chs. Point for the adjusted posi-
tion of Angle Point No. 2.

Set an iron post, 28 ins.
long, 2½ ins. diam., 22 ins.
in the ground, with brass cap
mkd.

AP 2 T24N
 R24E
 S 5

1976

Set a steel fence post, 6 ft.
long, alongside the iron post.

S. 16° 59' E., 25.04 chs. Point for the adjusted posi-
tion of Angle Point No. 3.

Set an iron post, 28 ins. long,
2½ ins. diam., 22 ins. in the
ground, with brass cap mkd.

AP 3 T24N
 R24E
 S 5

1976

Set a steel fence post, 6 ft.
long, alongside the iron post.