REESTABLISHMENT OF THE ORIGINAL MEANDER LINES IN SECS. 5, 17 AND 19, T. 24 N., R. 24 E., MDM, NEVADA

	IN SECS. 5, 17 AND 19, T. 24 N., R. 24 E., MDM, NEVADA
CHAINS	S. 56° 43' W., 17.17 chs. Point for the adjusted position of Angle Point No. 3.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	AP 3 / T24N R24E S 19
	1976
	S. 49° 17' W., 26.25 chs. The meander cor. of secs. 19 and 30.
	THE SURVEY OF SECTION 5A T. 24 N., R. 24 E., MOUNT DIABLO MERIDIAN, NEVADA
	From the meander cor. of secs. 5 and 8.
	S. 84° 51' W., on the S. bdy. of sec. 5A.
	Over nearly level lake bottom, covered with native grasses.
36.37	Point for the N. $\frac{1}{4}$ sec. cor. of sec. 8, is at 40.00 chs. E. in departure from the closing cor. of secs. 5 and 8 and on the N-S center line of sec. 8.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 5A
	C 1/4 S 8
	C T24N R24E
	1976
76.53	The closing cor. of secs. 7 and 8, hereinbefore described
116.67	Point for the N. $\frac{1}{4}$ sec. cor. of sec. 7, at midpoint bet. the closing cors. and on the N - S center line of sec. 7.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 5A C 1/4 S 7 C T24N R24E
	1976