

DEPENDENT RESURVEY OF THE WEST BOUNDARY,
T. 13 N., R. 21 E., MDM, NEVADA

CHAINS 33.60	Top of ascent, bears E. and W.; desc. along W. slope.
40.18	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an old mound of stone. There is no remaining evidence of the original wooden post and bearing trees. This position is harmoniously related to other identified corners along this boundary and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R20E R21E S 1 S 6 S 12 S 7</p> <p>1973</p> </div>
	<p>N. 0° 04' W., bet. secs. 1 and 6.</p> <p>Over rolling land, through medium sagebrush; desc. along W. slope.</p>
22.30	Graded road, bears NE. and WSW.
34.20	Graded road, bears E. and W.; asc. over gently rolling SW. slope, changing to W. slope.
40.20	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with a wooden post, 2x2x48 ins. long, firmly set in a mound of stone, mkd. with illegible scribe marks.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T13N R20E R21E ¼ S 1 S 6</p> <p>1973</p> </div> <p>reset the original wooden post, inverted, alongside the iron post.</p>
	<p>N. 0° 05' E., beginning new measurement.</p>
	Ascend over broken SW. slope, through medium sagebrush.