

Dependent Resurvey, Portion, S. Bdy.,
T. 12 N., R. 29 E., Mt. Diablo Mer., Nevada

CHAINS
30.50

Top of ditch bank, 10 lks. wide, bears N. 50° W. and S. 50° E.; desc. over E. slope.

36.20

Old Highway 95, paved, 20 lks. wide, bears N. 30° W. and S. 30° E.

40.22

The 1904 $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite stone, 20 x 6 x 6 ins., firmly set, top flush with the ground, mkd. $\frac{1}{4}$ on N. face. The 1929 resurvey by Ridgeway changed this cor. to function as the $\frac{1}{4}$ sec. cor. of sec. 31 only.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 12 N R 29 E
 $\frac{1}{4}$ S 31

1973

Deposit the original mkd. stone alongside the iron post.

Cor. falls 1 lk. N. of a fence line bearing E. and W.

East, beginning new measurement.

Desc. over E. slope.

0.39

The meander cor. of secs. 6 and 31, established by Franks and Mullen in 1904, monumented with a granite stone, 19 x 8 x 5 ins., firmly set, protruding 2 ins. above ground, and in a sunken mound of stone, 1 ft. base, 6 ins. high, mkd. MC on W., and 6 grooves on N. and S. faces. Ridgeway did not recover this cor. in 1929, but his survey changed its function to that of a meander cor. for sec. 31 only. It now also becomes Angle Pt. No. 4 of Tract No. 40.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.

T 12 N R 29 E
S 31 TR-40
AP-4
MC
S 6
T 11 N
1973

Deposit the original mkd. stone alongside the iron post.

Cor. falls 1 lk. N. of a fence bearing E. and W.

(Restoring a portion of the 1929 survey
by George W. Ridgeway, U.S. Cadastral Engineer)

East, on the N. bdy. of sec. 6, identical with a portion of line 4-5 of Tract No. 40, T. 12 N., R. 29 E.

Desc. over E. slope, changing to ESE.